MSB-C50

ACCESS OCEANIA

MANUAL SECURITY BARRIER
WITHSTANDS THE IMPACT OF A 7.5-TONNE HGV AT 48 KM/H
LENGTH 2 TO 6 M



Low and simplified maintenance | Installation and sealing in 24 hours | **High security level without a power supply** | Effortless opening in both directions of travel | Designed for regular operation

STANDARD CHARACTERISTICS

- **Arm:** Steel 120x120mm
- **Posts:** Thick steel Ø 250 mm
- **Treatment:**
  - Arm: galvanised steel and thermo-lacquering
  - Posts: zinc plating and thermo-lacquering
- **Opening:** In both directions of travel 180°
- **Lock:** Lockable by padlock in closed position



ACCESS OCEANIA

SUPPLIED & SUPPORTED IN NEW ZEALAND BY ACCESS X
Jayden Boylan · Commercial Director M 027 700 8668 jaydenb@accessx.co.nz
accessx.co.nz · 0800 322 269 · Unit 1, 13 Beatrice Tinsley Crescent, Rosedale, Auckland 0632

MSB-C50

TECHNICAL SPECIFICATION

Resistance	667,000 J
Paint	RAL 7016 polyurethane paint
Widths	From 2 to 6 m
Lock	Closing pin

CERTIFICATION

Resistance certified by crash test:

7.5 tonnes at 48 km/h
Tested in a shallow version

OPTIONAL FEATURES

Customisation

- Polyester paint (RAL choice)
- Two-tone posts / arm
- Position contact
- Pin lockable by padlock
- Reflective tape

INSTALLATION



